

OBT-6155



Model	OBT6155
Rated power	90W / 150W / 250W / 350W / 450W / 550W / 650W
Power consumption	160W/ 260W / 450W / 700W / 950W / 1200W / 1600W
Speaker outputs	70V,100V & 4~16
Input Sensitivity & Impedance	MIC 1,2:5mV/600 ,unbalanced 6.35 Screw Input AUX 1,2: 350mV/10K ,unbalanced RCA screw input
Output Sensitivity & Impedance	Mlx out:1000mV/470 ,unbalanced RCA screw output
Overload source electromotive force	MIC 1,2: 12dB,unbalanced 6.35 screw input AUX 1,2: 20dB,unbalanced RCA screw input MP3: 20dB,unbalanced input
Tone	Bass:10dB at 100Hz Treble:10dB at 10KHz
Frequency response	50Hz 16KHz(+1dB, -3dB)
S/N ratio	MIC 1,2:66dB;AUX 1,2:80dB
THD	1KHz 0.5%,1/3 Output Power Consumption
Muting function	MIC 1 overrides other input signals/0-30 dB adjustable
Crosstalk	50dB
Cooling	Forced air from front to rear, start built-in fan when radiator temperature reaches 45 degrees
Protection	Over heat,over load & short circuit
Power supply	AC 220V/50Hz
Dimensions(W * D* H	484 450 88mm
Weight	11Kg / 11.12Kg / 11.85Kg / 13.73Kg / 17Kg / 17.56Kg / 19.6Kg
Material	Black aluminum panel,SPCC cold rolled chassis